

Single Row Tapered Roller Bearings
Dalian JinYu HuaYang Industry Co., Ltd.
Tel: 86 411 84580998 / 66005509 / 86 13610855458
E-mail: hunaiwen@wjybearing.com
Website: www.jyhy-group.com

Bearing No.	Dimensions(mm)				Basic Load Rating(kN)		Weight (kg)
	d	D	B	T	Cr	Cor	
20007920	100	140	25	25	102	167	1.13
30220	100	180	34	37	262	340	3.56
30320	100	215	47	51.5	405	495	8.09
32020	100	150	32	32	190	281	1.87
32220	100	180	46	49	345	490	5.31
32320	100	215	73	77.5	610	840	13.2
33020	100	150	39	39	253	390	2.36
33220	100	180	63	63	430	655	6.58
20007121	105	160	33	35.4	171	256	2.5
30221	105	190	36	39	292	365	4.47
30321	105	225	49	53.5	430	530	9.38
32021	105	160	35	35	199	320	2.38
32221	105	190	50	53	385	555	6.34
32321	105	225	77	81.5	660	915	15
32321X3	105	215	73	78	550	755	12.3
33021	105	160	43	43	266	405	2.98
33021/YA6	105	160	43	43	266	405	2.98
33021/YA6-1	105	160	43	43	266	405	2.98
30222	110	200	38	41	320	430	5.27
30322	110	240	50	54.5	470	580	11.1
31322	110	240	57	63	470	595	12.5
32022	110	170	38	38	231	365	3.08
32022/YA8	110	170	38	38	216	390	3.11
32022X2A	110	170	36	38.4	198	297	3.1
32222	110	200	53	56	465	695	7.62
32222/YA8	110	200	53	56	415	600	7.58
32322	110	240	80	84.5	735	1030	18
32922X2A	110	150	24	25.4	88	138	1.18
33022	110	170	47	47	300	465	3.75
33022X3A/HA	110	190	49	49	360	560	5.87
33122	110	180	56	56	350	595	5.56
30623	115	190	49	49	282	440	5.13
30224	120	215	40	43.5	330	445	6.32
30324	120	260	55	59.5	565	710	14.2

31324	120	260	62	68	540	690	15.6
32024	120	180	38	38	237	395	3.31
32024X2A	120	180	36	38.4	230	325	3.66
32224	120	215	58	61.5	480	720	9.6
32324	120	260	86	90.5	845	1190	22.4
32924	120	165	29	29	189	320	1.79
33024	120	180	48	48	295	530	4.07
30226	130	230	40	43.75	360	480	7.02
30326	130	280	58	63.75	645	815	17.4
31326	130	280	66	72	620	805	18.9
32026	130	200	45	45	340	580	5.06
32026X2A	130	200	42	45.5	271	420	4.66
32226	130	230	64	67.75	555	845	11.8
32326/YA6	130	280	93	99.5	870	1250	26.4
32926X2A	130	180	30	32.5	150	249	2.31
7526EY	130	230	66	67.75	570	810	11.9
30228	140	250	42	45.75	405	540	8.8
30328	140	300	62	67.75	740	945	21.2
30628	140	230	57	58	400	660	8.97
30628R	140	230	57	58	400	660	9.2
31328	140	300	70	77	695	900	23.4
31328X2A	140	300	82	90	660	915	29
32028	140	210	45	45	330	560	5.84
32028X2A	140	210	42	45.5	276	440	4.94
32228	140	250	68	71.75	650	1000	14.7
32328	140	300	102	107.75	1090	1630	35.8
32928	140	190	32	32	206	390	2.55
32928X2A	140	190	30	32.5	154	257	2.43
30230	150	270	45	49	450	605	11.2
30330	150	320	65	72	815	1050	25.5
31330	150	320	75	82	810	1060	27.5
32030	150	225	48	48	365	635	6.4
32030X2	150	225	45	48.5	280	454	6.84
32230	150	270	73	77	735	1140	18.4
32330	150	320	108	114	1280	1880	42.2
32930	150	210	38	38	270	465	3.83
32930X2A	150	210	36	38.5	220	385	4.56
30232	160	290	48	52	510	695	13.4
30332	160	340	68	75	915	1180	29.5
30632	160	375	79.4	86.55	870	1050	40.7
30632X2	160	375	79.4	86.55	870	1050	41.8
31332	160	340	79	88	825	1080	29.9

32032	160	240	51	51	415	730	7.69
32032X2A-1	160	240	48	51.5	375	630	7.67
32232	160	290	48	52	925	1490	23.3
32332	160	340	114	121	1540	2230	51.7
32932X2A	160	220	36	38.5	232	400	3.79
30234	170	260	54	57.5	605	845	17
32034	170	220	25	27	520	870	10.6
32034/P4YA6	170	260	57	57	520	870	10.6
32034X2A	170	260	57	57	430	750	10.1
32234	170	310	52	57	1010	1630	30
32334/YA6	170	360	120	128	1430	2120	63.5
32934	170	230	38	38	280	560	4.51
32934X2A	170	230	36	38.5	235	415	3.864
30236	180	320	52	57	590	820	17.8
31336	180	380	88	98	1050	1500	46.4
32036	180	280	64	64	610	1070	13.9
32036X2A	180	280	60	64.5	520	860	13
32036X3A	180	290	63.5	65	580	1010	15.6
32236	180	320	86	91	1020	1670	32.3
32936	180	250	45	45	345	725	6.7
T4DB 180	180	240	30	32	245	250	3.55
30238	190	340	55	60	740	1040	20.6
32038X2A	190	290	60	64.5	520	882	15.28
32038X2A-1	190	290	60	64.5	380	610	10.5
32238	190	340	92	97	1100	1080	36.1
32938	190	260	42	45.5	335	745	6.94
32938X2A	190	290	46	51	350	670	6.52
30240	200	360	58	64	780	1100	25.4
32040X2A	200	310	66	70.5	575	1040	18.2
32240	200	360	98	104	1350	2144	42.6
32940	200	280	51	51	455	935	9.56
32940X2A	200	280	48	51.5	380	742	8.86
T4DB 200	200	270	34	37	325	580	5.5
30244	220	400	65	72	975	1370	36.8
30244A/YA6	220	400	65	73	855	1180	37.6
32044X2A	220	340	72	76.5	780	1330	23.3
32244	220	400	108	114	1650	2770	62.7
32944X2A	220	300	48	51.5	390	835	10.1
T2DC 220	220	285	40	41	385	800	6.5
2007148S	240	360	76	76	845	1410	24.9
2007148SY	240	360	76	76	845	1410	24.7
32048X2A	240	360	72	76.5	770	1400	23.8

32248	240	440	120	127	1900	3300	82.5
32948	240	320	51	51	500	1050	11.5
32948X2A	240	320	48	51	390	790	10.8
32948X2A/P4	240	320	48	51	360	790	11.1
T4EB 240	240	320	39	42	420	800	8.5
30352	260	540	102	114	2015	2730	113
30352X2	260	540	102	109	2050	2950	108
32052X2A	260	400	82	87.7	1050	1960	37.8
32252	260	480	130	137	2160	3650	105
32252X2/HC	260	480	141	133.5	2280	3750	101
32952X2A	260	360	60	64.5	595	1250	19.2
32056X2A	280	420	82	87.7	1000	1840	39.6
32956X2A	280	380	60	64.5	600	1250	21.3
30660	300	540	140	149	2680	4700	142
32060	300	460	100	100	1460	2740	56.6
32060X2A	300	460	95	100.7	1310	2400	57
32960	300	420	72	74.5	710	1810	30.2
32960X3B/P5	300	440	70	73	860	1460	34.2
30664	320	620	125	141	2780	4600	183
32064	320	480	100	100	1540	2940	62.7
32964	320	440	76	76	1000	2300	34.5
31068X2	340	520	82	86	1200	2050	73.9
32968	340	460	76	76	1000	2350	36.5
30672	360	680	150	165	3620	6250	262
30672/P5	360	530	66	80	1030	1900	53.2
31072X2	360	540	82	86	1270	2200	73.1
32972	360	480	76	76	970	2220	38.5
30680	400	500	57	60	460	950	25.1
30680-1	400	750	115	130	2660	4180	222
31084X2	420	620	90	95	1560	2930	88.3
31084X2/P5	420	620	90	95	1560	2940	88.3
30692	460	860	190	210	5590	10100	512
30696	480	950	225	240	6980	12500	761
T2GB500	500	720	100	110	2090	4100	128
318/530X3	530	670	95	100	1590	4500	81.6
319/530X2	530	710	82	88	1560	3150	81.5
306/560	560	1080	235	265	8910	15700	1063
306/630	630	920	128	134	3410	7100	286
329/630	630	850	132	132	3080	7150	200
T3GB630	630	920	128	135	3520	7450	289
306/680	680	1000	188	190	5580	12500	486
319/710	710	950	106	114	2860	6900	210

306/760/HC	760	890	75	78	1360	3520	78.3
318/850X2	850	1030	88	90	2200	5900	140
306/900/HC	900	1280	170	190	6430	14600	71.8
T3GB900	900	1180	122	122	3850	9000	325
306/1000	1000	1420	195	210	8100	18000	966
306/1270	1270	1465	69	73	2100	6920	71.8
306/1270-1	1270	1465	100	100	3120	10500	266